

View Online at <https://aerobasegroup.com/nsn/6625-00-740-6188>

**Circuit Current For Which Designed:**

Dc

**Dielectric Withstanding Voltage In Volts:**

2000.0

**Overall Length:**

2.150 inches

**Mounting Hole Diameter:**

0.112 inches

**Scale Division Quantity:**

45 single indicator single range

**Overall Diameter:**

2.695 inches

**Environmental Protection:**

Dust resistant

**Mounting Bolt Circle Diameter:**

2.440 inches

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Three hole/stud bolt circle

**Sensitivity Rating:**

200.0 microamperes

**Dial Scale Marking Color:**

Green single indicator single range

**Accuracy In Percent:**

-2.0/+2.0 at full scale single indicator single range

**Meter Depth Behind Mounting Flange:**

1.405 inches

**Meter Body Diameter Behind Mounting Flange:**

2.210 inches

**Movement Type:**

Moving coil, permanent magnet

**Background Color:**

Black single indicator single range

**Pointer Color:**

Black single indicator single range

**Power Source:**

External

**Mounting Facility Type And Quantity:**

3 threaded hole

**Scale Graduation Type:**

Linear single indicator single range

**Measurement Range:**

+10.0/+200.0 microamperes, dc single indicator single range

**Scale Selection Method:**

Terminal

**Features Provided:**

Magnetic shield and self-illumination facility

**Circuit Attachment Method And Quantity:**

2 solderless lug

**Material:**

Steel

**Nuclear Hardness Critical Feature:**

Nonhardened

**Style Designator:**

Round flush mtg

**Fsc Application Data:**

Test set, electronic equipment

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A310a0