

View Online at <https://aerobasegroup.com/nsn/6625-00-752-7556>

Circuit Current For Which Designed:

Dc

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.875 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.875 inches

Overall Height:

2.375 inches

Overall Width:

2.375 inches

Mounting Hole Diameter:

0.125 inches

Scale Division Quantity:

25 single indicator single range

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Sensitivity Rating:

100.0 millivolts

Dial Scale Marking Color:

White single indicator single range

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

1.770 inches

Meter Body Diameter Behind Mounting Flange:

2.219 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

Black single indicator single range

Mounting Facility Type And Quantity:

4 unthreaded hole

Measurement Range:

+0.0/+50.0 microamperes, dc single indicator single range

Features Provided:

Zero adjuster and self-illumination facility

Circuit Attachment Method And Quantity:

2 threaded stud

Special Markings:

Crystal current

Material:

Plastic

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A310a0