## NSN 6625-00-752-7822

Ammeter - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/6625-00-752-7822

Circuit Current For Which Designed:
Ac
Dielectric Withstanding Voltage In Volts:
3000.0
Overall Length:
2.650 inches
Scale Division Quantity:
40 single indicator single range
Frequency Rating:
60.0 hertz
Mounting Stud Length:
0.500 inches
Overall Diameter:
2.695 inches
Environmental Protection:
Cold resistant and heat resistant and shock resistant and submersible and vibration resistant and watertight
Mounting Bolt Circle Diameter:
2.440 inches
Furnished Items And Quantity:
Mtg hdw 3
Indicator Type:
Dial w/pointer
Installation Design:
Panel
Mounting Arrangement Style:
Three hole/stud bolt circle
Frequency Response Range:
+0.000025/+30.000000 megahertz
Sensitivity Rating:
500.0 millivolts
Dial Scale Marking Color:
Black single indicator single range
Accuracy In Percent:
-2.0/+2.0 at full scale single indicator single range
Unable To Decode:
Unable to decode or unable to decode
Meter Depth Behind Mounting Flange:
2.250 inches
Meter Body Diameter Behind Mounting Flange:
2.210 inches
Movement Type:

Moving coil, permanent magnet

## NSN 6625-00-752-7822

Ammeter - Page 2 of 3



<u> </u>	ui o
Background Color:	
White single indicator single range	
Pointer Color:	
Black single indicator single range	
Power Source:	
External	
Mounting Facility Type And Quantity:	
3 threaded stud	
Scale Graduation Type:	
Linear single indicator single range	
Measurement Range:	
+0.0/+8.0 amperes, ac single indicator single range	
Mounting Stud Diameter:	
0.112 inches	
Scale Selection Method:	
Terminal	
Features Provided:	
Luminous scale marking and magnetic shield and zero adjuster	
Movement Suspension Method:	
Jewel pivot base	
Circuit Attachment Method And Quantity:	
2 threaded stud	
Phase:	
Single	
Special Features:	
Ruggedized	
Material:	
Steel	
Nuclear Hardness Critical Feature:	
Nonhardened	
Surface Treatment:	
Enamel semigloss	
Surface Treatment Specification:	
Mil-f-14072 military specification all treatment responses	
Style Designator:	
Round flush mtg	
Test Data Document:	
81349-mil-m-10304 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification type data in specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification (includes engineering type bulletins).	fication
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	1
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).	
Specification Data:	
81349-mil-m-10304/8 government specification	

Shelf Life:

**Fsc Application Data:** Test set, elect. Equip.

## NSN 6625-00-752-7822

Ammeter - Page 3 of 3



	U	nit	Of	Measure	:
--	---	-----	----	---------	---

--

Demilitarization:

No

Fiig:

A310a0

Mil-std (military Standard):

Mil-f-14072 spec.