## NSN 6625-00-753-2092

Voltmeter - Page 1 of 2

Dc

Overall Length: 2.650 inches

**Mounting Hole Diameter:** 

**Circuit Current For Which Designed:** 



View Online at https://aerobasegroup.com/nsn/6625-00-753-2092

0.125 inches
Scale Division Quantity:
30 single indicator single range
Overall Diameter:
2.695 inches
Mounting Bolt Circle Diameter:
2.440 inches
Installation Design:
Panel
Mounting Arrangement Style:
Three hole/stud bolt circle
Sensitivity Rating:
125.0 ohms per volt
Dial Scale Marking Color:
White single indicator single range
Accuracy In Percent:
-2.0/+2.0 at full scale single indicator all ranges
Meter Depth Behind Mounting Flange:
2.250 inches
Motor Pady Diameter Pohind Mounting Florida
Meter Body Diameter Behind Mounting Flange:
2.210 inches
2.210 inches
2.210 inches  Mounting Facility Type And Quantity:
2.210 inches  Mounting Facility Type And Quantity:  3 unthreaded hole
2.210 inches  Mounting Facility Type And Quantity:  3 unthreaded hole  Measurement Range:
2.210 inches  Mounting Facility Type And Quantity: 3 unthreaded hole  Measurement Range: +0.0/+3.0 volts, dc single indicator single range
2.210 inches  Mounting Facility Type And Quantity: 3 unthreaded hole  Measurement Range: +0.0/+3.0 volts, dc single indicator single range  Features Provided:
2.210 inches  Mounting Facility Type And Quantity:  3 unthreaded hole  Measurement Range: +0.0/+3.0 volts, dc single indicator single range  Features Provided:  Zero adjuster
2.210 inches  Mounting Facility Type And Quantity: 3 unthreaded hole  Measurement Range: +0.0/+3.0 volts, dc single indicator single range Features Provided: Zero adjuster  Circuit Attachment Method And Quantity:
2.210 inches  Mounting Facility Type And Quantity: 3 unthreaded hole  Measurement Range: +0.0/+3.0 volts, dc single indicator single range Features Provided: Zero adjuster Circuit Attachment Method And Quantity: 2 threaded stud
2.210 inches  Mounting Facility Type And Quantity: 3 unthreaded hole  Measurement Range: +0.0/+3.0 volts, dc single indicator single range Features Provided: Zero adjuster  Circuit Attachment Method And Quantity: 2 threaded stud  Special Markings:
2.210 inches  Mounting Facility Type And Quantity: 3 unthreaded hole  Measurement Range: +0.0/+3.0 volts, dc single indicator single range Features Provided: Zero adjuster  Circuit Attachment Method And Quantity: 2 threaded stud  Special Markings: Line at 2v
2.210 inches  Mounting Facility Type And Quantity: 3 unthreaded hole  Measurement Range: +0.0/+3.0 volts, dc single indicator single range Features Provided: Zero adjuster Circuit Attachment Method And Quantity: 2 threaded stud Special Markings: Line at 2v Radioactive Content:
2.210 inches  Mounting Facility Type And Quantity:  3 unthreaded hole  Measurement Range: +0.0/+3.0 volts, dc single indicator single range Features Provided: Zero adjuster  Circuit Attachment Method And Quantity: 2 threaded stud  Special Markings: Line at 2v  Radioactive Content: Contains radioactive material
2.210 inches  Mounting Facility Type And Quantity: 3 unthreaded hole  Measurement Range: +0.0/+3.0 volts, dc single indicator single range Features Provided: Zero adjuster  Circuit Attachment Method And Quantity: 2 threaded stud  Special Markings: Line at 2v  Radioactive Content: Contains radioactive material  Style Designator:
2.210 inches  Mounting Facility Type And Quantity: 3 unthreaded hole  Measurement Range: +0.0/+3.0 volts, dc single indicator single range Features Provided: Zero adjuster Circuit Attachment Method And Quantity: 2 threaded stud Special Markings: Line at 2v Radioactive Content: Contains radioactive material Style Designator: Round flush mtg
2.210 inches  Mounting Facility Type And Quantity:  3 unthreaded hole  Measurement Range: +0.0/+3.0 volts, dc single indicator single range Features Provided: Zero adjuster  Circuit Attachment Method And Quantity: 2 threaded stud  Special Markings: Line at 2v  Radioactive Content: Contains radioactive material  Style Designator: Round flush mtg  Reference Number Differentiating Characteristics:

## NSN 6625-00-753-2092

Voltmeter - Page 2 of 2



_					
•	n	<b>0</b> 1	•	12	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A310a0