

View Online at <https://aerobasegroup.com/nsn/6625-00-756-1018>

Circuit Current For Which Designed:

Dc

Dielectric Withstanding Voltage In Volts:

3000.0

Overall Depth:

4.000 inches

Overall Length:

8.750 inches

Overall Width:

7.750 inches

Indicator Type:

Dial w/pointer

Installation Design:

Bench

Sensitivity Rating:

1000.0 ohms per volt

Dial Scale Marking Color:

Black single indicator all ranges

Accuracy In Percent:

-0.5 to 0.5 at full scale single indicator all ranges

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator all ranges

Pointer Color:

Black single indicator all ranges

Power Source:

Internal

Scale Graduation Type:

Nonlinear single indicator all ranges

Measurement Range:

+0.0 to 500.0 volts, dc single indicator 3rd range

Scale Selection Method:

Switch

Features Provided:

Electrostatic shield and magnetic shield and mirror scale and portable and zero adjuster

Circuit Attachment Method And Quantity:

2 binding post and 2 wire lead

Special Markings:

Switch markings; 2, 5, 10, 20, 50

Material:

Plastic

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Portable

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fii:

A310a0