

View Online at <https://aerobasegroup.com/nsn/6625-00-756-3791>

**Circuit Current For Which Designed:**

Ac

**Overall Length:**

3.100 inches

**Mounting Hole Diameter:**

0.125 inches

**Frequency Rating:**

Between 55.0 hertz and 65.0 hertz

**Overall Diameter:**

2.703 inches

**Mounting Bolt Circle Diameter:**

2.440 inches

**Furnished Items And Quantity:**

Nut 9; washer 9

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Three hole/stud bolt circle

**Dial Scale Marking Color:**

Black single indicator all ranges

**Accuracy In Percent:**

-3.0 to 3.0 at full scale single indicator all ranges

**Meter Depth Behind Mounting Flange:**

1.500 inches

**Meter Body Diameter Behind Mounting Flange:**

2.210 inches

**Movement Type:**

Moving iron vane

**Background Color:**

White single indicator all ranges

**Pointer Color:**

Black single indicator all ranges

**Power Source:**

External

**Mounting Facility Type And Quantity:**

3 unthreaded hole

**Scale Graduation Type:**

Nonlinear single indicator all ranges

**Measurement Range:**

+0.0 to 600.0 volts, ac single indicator 2nd range

**Scale Selection Method:**

Terminal

**Features Provided:**

External shunting and zero adjuster

**Movement Suspension Method:**

Taut band

**Circuit Attachment Method And Quantity:**

3 threaded stud

**Special Features:**

Ruggedized

**Special Markings:**

150 v and 600 v on back of meter

**Material:**

Steel

**Nuclear Hardness Critical Feature:**

Nonhardened

**Surface Treatment:**

Enamel

**Style Designator:**

Round flush mtg

**Supplementary Features:**

Internal rectifiers

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiiig:**

A310a0