

View Online at <https://aerobasegroup.com/nsn/6625-00-757-6479>

Circuit Current For Which Designed:

Dc

Overall Length:

2.526 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

5.250 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.000 inches

Overall Height:

4.340 inches

Overall Width:

5.720 inches

Mounting Stud Length:

0.500 inches

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Dial Scale Marking Color:

Black single indicator all ranges

Accuracy In Percent:

-5.0 to 5.0 at full scale single indicator all ranges

Meter Depth Behind Mounting Flange:

1.156 inches

Meter Body Diameter Behind Mounting Flange:

2.765 inches

Movement Type:

Moving iron vane

Background Color:

White single indicator all ranges

Pointer Color:

Red single indicator all ranges

Mounting Facility Type And Quantity:

4 threaded stud

Scale Graduation Type:

Nonlinear single indicator all ranges

Measurement Range:

-0.0001 to 10.0000 volts, root mean square single indicator 3rd range

Mounting Stud Diameter:

0.128 inches

Features Provided:

Zero adjuster

Movement Suspension Method:

Taut band

Circuit Attachment Method And Quantity:

2 threaded stud

Material:

Plastic

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular flush mtg

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0