

View Online at <https://aerobasegroup.com/nsn/6625-00-762-5753>

**Circuit Current For Which Designed:**

Dc

**Dielectric Withstanding Voltage In Volts:**

3000.0

**Overall Length:**

2.650 inches

**Mounting Hole Diameter:**

Between 0.120 inches and 0.130 inches

**Scale Division Quantity:**

50 single indicator 1st range

**Overall Diameter:**

2.695 inches

**Environmental Protection:**

Corrosion resistant and dust resistant and humidity resistant

**Mounting Bolt Circle Diameter:**

2.440 inches

**Furnished Items And Quantity:**

Clip 1; terminal board 1; nut 2

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Three hole/stud bolt circle

**Sensitivity Rating:**

1.0 milliamperes

**Dial Scale Marking Color:**

Black single indicator all ranges

**Accuracy In Percent:**

-2.0 to 2.0 at full scale single indicator all ranges

**Meter Depth Behind Mounting Flange:**

1.250 inches

**Meter Body Diameter Behind Mounting Flange:**

2.210 inches

**Background Color:**

White single indicator all ranges

**Pointer Color:**

Black single indicator all ranges

**Mounting Facility Type And Quantity:**

3 unthreaded hole

**Scale Graduation Type:**

Linear single indicator all ranges

**Measurement Range:**

+0.0 to 50.0 volts single indicator 1st range

**Scale Selection Method:**

Terminal

**Features Provided:**

Zero adjuster

**Circuit Attachment Method And Quantity:**

2 threaded stud

**Special Features:**

Ruggedized indi

**Nuclear Hardness Critical Feature:**

Nonhardened

**Special Test Features:**

Conforms to mil-m-10304/4, type mr26w001dcmar

**Style Designator:**

Round flush mtg

**Fsc Application Data:**

Test set, transponder set

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fii:**

A310a0