

View Online at <https://aerobasegroup.com/nsn/6625-00-762-5753>

Circuit Current For Which Designed:

Dc

Dielectric Withstanding Voltage In Volts:

3000.0

Overall Length:

2.650 inches

Mounting Hole Diameter:

Between 0.120 inches and 0.130 inches

Scale Division Quantity:

50 single indicator 1st range

Overall Diameter:

2.695 inches

Environmental Protection:

Corrosion resistant and dust resistant and humidity resistant

Mounting Bolt Circle Diameter:

2.440 inches

Furnished Items And Quantity:

Clip 1; terminal board 1; nut 2

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Three hole/stud bolt circle

Sensitivity Rating:

1.0 milliamperes

Dial Scale Marking Color:

Black single indicator all ranges

Accuracy In Percent:

-2.0 to 2.0 at full scale single indicator all ranges

Meter Depth Behind Mounting Flange:

1.250 inches

Meter Body Diameter Behind Mounting Flange:

2.210 inches

Background Color:

White single indicator all ranges

Pointer Color:

Black single indicator all ranges

Mounting Facility Type And Quantity:

3 unthreaded hole

Scale Graduation Type:

Linear single indicator all ranges

Measurement Range:

+0.0 to 50.0 volts single indicator 1st range

Scale Selection Method:

Terminal

Features Provided:

Zero adjuster

Circuit Attachment Method And Quantity:

2 threaded stud

Special Features:

Ruggedized indi

Nuclear Hardness Critical Feature:

Nonhardened

Special Test Features:

Conforms to mil-m-10304/4, type mr26w001dcmar

Style Designator:

Round flush mtg

Fsc Application Data:

Test set, transponder set

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fii:

A310a0