

View Online at <https://aerobasegroup.com/nsn/6625-00-763-8856>

Circuit Current For Which Designed:

Ac

Overall Length:

2.840 inches

Scale Division Quantity:

10 single indicator single range

Mounting Stud Length:

0.500 inches

Overall Diameter:

3.495 inches

Environmental Protection:

Shock resistant and vibration resistant

Mounting Bolt Circle Diameter:

3.160 inches

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Three hole/stud bolt circle

Sensitivity Rating:

1000.0 ohms per volt

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0 to 2.0 at full scale single indicator single range

Unable To Decode:

Unable to decode or unable to decode

Meter Depth Behind Mounting Flange:

2.630 inches

Meter Body Diameter Behind Mounting Flange:

2.800 inches

Movement Type:

Moving iron vane

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

3 threaded stud

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+110.0 to 130.0 volts, ac single indicator single range

Mounting Stud Diameter:

0.138 inches

Features Provided:

Magnetic shield and zero adjuster

Movement Suspension Method:

Taut band

Circuit Attachment Method And Quantity:

2 threaded stud

Special Features:

Ruggedized

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Round flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A310a0