

View Online at <https://aerobasegroup.com/nsn/6625-00-764-3705>

Circuit Current For Which Designed:

Dc

Dielectric Withstanding Voltage In Volts:

500.0

Overall Length:

2.495 inches

Overall Height:

0.504 inches

Overall Width:

1.600 inches

Mounting Hole Diameter:

0.125 inches

Scale Division Quantity:

30 single indicator single range

Environmental Protection:

Humidity resistant

Distance Between Mounting Facility Centers:

Between 1.280 inches and 1.290 inches

Barrel Width:

1.600 inches

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Two hole/stud

Sensitivity Rating:

1000.0 ohms per volt

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-3.0 to 3.0 at full scale single indicator all ranges

Meter Depth Behind Mounting Flange:

1.705 inches

Meter Body Width Behind Mounting Flange:

1.600 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

2 threaded hole

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+0.0 to 60.0 volts, dc single indicator single range

Scale Selection Method:

Terminal

Meter Body Height Behind Mounting Flange:

0.895 inches

Meter Barrel Depth:

1.605 inches

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 solder stud

Special Markings:

Left hand terminal: + sign

Material:

Plastic

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular flush mtg barrel, right

Fsc Application Data:

Electrical, electronic properties measuring and test instruments

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0