

View Online at <https://aerobasegroup.com/nsn/6625-00-764-8216>

Current Type:

Ac

Frequency Rating:

Between 50.0 hertz and 400.0 hertz

Accessory Components And Quantity:

Light filter 1; divider probe 1; probe tip assortment 1

Voltage Rating:

Between 115.0 volts and 230.0 volts

Beam Quantity:

1

Mounting Method:

Portable type

Accuracy Range In Percent:

-3.0/+3.0

Screen Size:

5.000 in.

Sweep Circuits:

Included

Generator Driven Feature:

Included

Sweep Circuit Type:

Horizontal and vertical

Trigger Sweep Polarity Switch:

Included

Expanded Sweep:

Provided

Amplifier Deflection Sensitivity Provision:

Not provided

Input Intensity Modulation Feature:

Not provided

Plate Direct Connection Deflection Sensitivity Provision:

Not provided

Frequency Response Rating:

Provided

X-axis Frequency Response Rating:

Between 0.0 kilohertz and 450.0 kilohertz

Y-axis Frequency Response Rating:

Between 0.0 kilohertz and 450.0 kilohertz

Amplifier Input Impedance Rating Provision:

Provided

X-axis Input Impedance Rating:

1.0 megohms

Y-axis Input Impedance Rating:

1.0 megohms

Amplitude Calibrating Voltage Waveform:

Square wave

Calibrating Peak To Peak Amplitude:

100.0 millivolts

Measurement Range Quantity:

2

Measurement Range Steps:

1 mv to 20 v per cm

Calibrated Screen Scale:

Not included

Trace Storage Tube:

Not included

Camera Recording Device Accommodation:

Not provided

Phase:

Single

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T320-g