

View Online at <https://aerobasegroup.com/nsn/6625-00-764-8216>

**Current Type:**

Ac

**Frequency Rating:**

Between 50.0 hertz and 400.0 hertz

**Accessory Components And Quantity:**

Light filter 1; divider probe 1; probe tip assortment 1

**Voltage Rating:**

Between 115.0 volts and 230.0 volts

**Beam Quantity:**

1

**Mounting Method:**

Portable type

**Accuracy Range In Percent:**

-3.0/+3.0

**Screen Size:**

5.000 in.

**Sweep Circuits:**

Included

**Generator Driven Feature:**

Included

**Sweep Circuit Type:**

Horizontal and vertical

**Trigger Sweep Polarity Switch:**

Included

**Expanded Sweep:**

Provided

**Amplifier Deflection Sensitivity Provision:**

Not provided

**Input Intensity Modulation Feature:**

Not provided

**Plate Direct Connection Deflection Sensitivity Provision:**

Not provided

**Frequency Response Rating:**

Provided

**X-axis Frequency Response Rating:**

Between 0.0 kilohertz and 450.0 kilohertz

**Y-axis Frequency Response Rating:**

Between 0.0 kilohertz and 450.0 kilohertz

**Amplifier Input Impedance Rating Provision:**

Provided

**X-axis Input Impedance Rating:**

1.0 megohms

**Y-axis Input Impedance Rating:**

1.0 megohms

**Amplitude Calibrating Voltage Waveform:**

Square wave

**Calibrating Peak To Peak Amplitude:**

100.0 millivolts

**Measurement Range Quantity:**

2

**Measurement Range Steps:**

1 mv to 20 v per cm

**Calibrated Screen Scale:**

Not included

**Trace Storage Tube:**

Not included

**Camera Recording Device Accommodation:**

Not provided

**Phase:**

Single

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T320-g