

View Online at <https://aerobasegroup.com/nsn/6625-00-765-6232>

**Circuit Current For Which Designed:**

Dc

**Overall Length:**

2.250 inches

**Mounting Hole Diameter:**

0.172 inches

**Overall Diameter:**

3.437 inches

**Environmental Protection:**

Shock resistant and vibration resistant

**Mounting Bolt Circle Diameter:**

3.062 inches

**Furnished Items And Quantity:**

Nut 6

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Three hole/stud bolt circle

**Sensitivity Rating:**

5.0 amperes

**Dial Scale Marking Color:**

Black single indicator all ranges

**Accuracy In Percent:**

-2.0/+2.0 at full scale single indicator all ranges

**Meter Depth Behind Mounting Flange:**

1.250 inches

**Meter Body Diameter Behind Mounting Flange:**

2.500 inches

**Movement Type:**

Moving coil, permanent magnet

**Background Color:**

White single indicator all ranges

**Pointer Color:**

Black single indicator all ranges

**Scale Marking:**

Top scale: 0, 25, 50, 75, 100, pct load; bot scale: 0, 50, 75, 100, 125, y pct load

**Mounting Facility Type And Quantity:**

3 unthreaded hole

**Scale Graduation Type:**

Nonlinear single indicator all ranges

**Features Provided:**

Zero adjuster

**Movement Suspension Method:**

Jewel pivot base

**Circuit Attachment Method And Quantity:**

2 threaded stud

**Special Features:**

Ruggedized

**Material:**

Steel

**Nuclear Hardness Critical Feature:**

Nonhardened

**Special Test Features:**

Conforms to mil-m-10304

**Style Designator:**

Round flush mtg

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A310a0