

View Online at <https://aerobasegroup.com/nsn/6625-00-765-9181>

Overall Length:

20.500 inches

Overall Height:

7.125 inches

Overall Width:

12.500 inches

Current Type:

Ac

Frequency Rating:

Between 48.0 hertz and 62.0 hertz

Accessory Components And Quantity:

Probe, voltage divider 2, 50 ohm bnc cable 18 in. Lg, bnc jack post 1, crt ornamental ring 1, instruction manual 1, operator manual 1, fuses 5

Voltage Rating:

Between 90.0 volts and 272.0 volts

Beam Quantity:

1

Graduation Interval:

Graduated 5 mv/div both axis

Mounting Method:

Carrying case

Accuracy Range In Percent:

-3.0/+3.0

Screen Size:

4.000

Sweep Circuits:

Included

Generator Driven Feature:

Included

Sweep Circuit Type:

Horizontal and vertical

Trigger Sweep Voltage Amplitude Rating:

200.0 millivolts

Trigger Sweep Polarity Switch:

Included

Expanded Sweep:

Provided

Amplifier Deflection Sensitivity Provision:

Not provided

Input Intensity Modulation Feature:

Provided

Visual Modulation Sensitivity Voltage Rating:

5.0 volts

Plate Direct Connection Deflection Sensitivity Provision:

Not provided

Frequency Response Rating:

Provided

X-axis Frequency Response Rating:

40.0 megahertz

Y-axis Frequency Response Rating:

5.0 megahertz

Amplifier Input Impedance Rating Provision:

Provided

X-axis Input Impedance Rating:

1.0 megohms

Y-axis Input Impedance Rating:

1.0 megohms

Amplitude Calibrating Voltage Waveform:

Square wave

Calibrating Peak To Peak Amplitude:

Between 0.1 volts and 1.0 volts

Calibrated Screen Scale:

Included

Trace Storage Tube:

Not included

Camera Recording Device Accommodation:

Provided

Phase:

Single

Special Features:

Oscilloscope is dual trace with two identical channels

Reference Data And Literature:

To 33a1-13-336-41

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T320-g