

View Online at <https://aerobasegroup.com/nsn/6625-00-765-9181>

**Overall Length:**

20.500 inches

**Overall Height:**

7.125 inches

**Overall Width:**

12.500 inches

**Current Type:**

Ac

**Frequency Rating:**

Between 48.0 hertz and 62.0 hertz

**Accessory Components And Quantity:**

Probe, voltage divider 2, 50 ohm bnc cable 18 in. Lg, bnc jack post 1, crt ornamental ring 1, instruction manual 1, operator manual 1, fuses 5

**Voltage Rating:**

Between 90.0 volts and 272.0 volts

**Beam Quantity:**

1

**Graduation Interval:**

Graduated 5 mv/div both axis

**Mounting Method:**

Carrying case

**Accuracy Range In Percent:**

-3.0/+3.0

**Screen Size:**

4.000

**Sweep Circuits:**

Included

**Generator Driven Feature:**

Included

**Sweep Circuit Type:**

Horizontal and vertical

**Trigger Sweep Voltage Amplitude Rating:**

200.0 millivolts

**Trigger Sweep Polarity Switch:**

Included

**Expanded Sweep:**

Provided

**Amplifier Deflection Sensitivity Provision:**

Not provided

**Input Intensity Modulation Feature:**

Provided

**Visual Modulation Sensitivity Voltage Rating:**

5.0 volts

**Plate Direct Connection Deflection Sensitivity Provision:**

Not provided

**Frequency Response Rating:**

Provided

**X-axis Frequency Response Rating:**

40.0 megahertz

**Y-axis Frequency Response Rating:**

5.0 megahertz

**Amplifier Input Impedance Rating Provision:**

Provided

**X-axis Input Impedance Rating:**

1.0 megohms

**Y-axis Input Impedance Rating:**

1.0 megohms

**Amplitude Calibrating Voltage Waveform:**

Square wave

**Calibrating Peak To Peak Amplitude:**

Between 0.1 volts and 1.0 volts

**Calibrated Screen Scale:**

Included

**Trace Storage Tube:**

Not included

**Camera Recording Device Accommodation:**

Provided

**Phase:**

Single

**Special Features:**

Oscilloscope is dual trace with two identical channels

**Reference Data And Literature:**

To 33a1-13-336-41

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T320-g