Electrical Frequency Meter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-772-6019

| (| Circuit Current For Which Designed: |
|---|-------------------------------------------------|
| A | Ac |
| C | Overall Length: |
| 2 | 2.625 inches |
| Ν | Nounting Hole Diameter: |
| C | 0.125 inches |
| F | Frequency Rating: |
| 6 | S0.0 hertz |
| C | Overall Diameter: |
| 2 | 2.688 inches |
| Γ | Nounting Bolt Circle Diameter: |
| 2 | 2.440 inches |
| E | End Application: |
| A | An/tps-63 radar system |
| I | ndicator Type: |
| ١ | /ibrating reed |
| I | nstallation Design: |
| F | Panel |
| F | Register Quantity: |
| 1 | |
| | Nounting Arrangement Style: |
| | Three hole/stud bolt circle |
| | Frequency Response Range: |
| | -58.000/+62.000 hertz |
| | Resonant Reed Quantity: |
| | |
| | Neter Depth Behind Mounting Flange: |
| | .844 inches |
| | Neter Body Diameter Behind Mounting Flange: |
| | 2.125 inches |
| | Novement Type: |
| | /ibrating reed |
| | Background Color: |
| | Black single indicator single range |
| | Mounting Facility Type And Quantity: |
| | 3 unthreaded hole |
| | Measurement Range: |
| | -58.0/+62.0 hertz single indicator single range |
| | Scale Selection Method: |
| | |
| | Criticality Code Justification: |
| ŀ | Feat |

NSN 6625-00-772-6019

Electrical Frequency Meter - Page 2 of 2



Circuit Attachment Method And Quantity:

2 solder stud

Operating Voltage Rating In Volts:

Between 100.0 ac and 130.0 ac

Special Features:

Weapon system essential; 0.25 watt power consumption.

Style Designator:

Round flush mtg

Supplementary Features:

525 ohms per v res

Specification Data:

09017-301992 manufacturers specification control

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A310a0