

View Online at <https://aerobasegroup.com/nsn/6625-00-773-0163>

**Circuit Current For Which Designed:**

Ac

**Overall Length:**

2.118 inches

**Mounting Hole Diameter:**

Between 0.120 inches and 0.130 inches

**Scale Division Quantity:**

60 single indicator 2nd range

**Overall Diameter:**

2.695 inches

**Environmental Protection:**

Cold resistant and heat resistant and shock resistant and vibration resistant

**Mounting Bolt Circle Diameter:**

2.440 inches

**Furnished Items And Quantity:**

Nut 3; lockwasher 3

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Three hole/stud bolt circle

**Sensitivity Rating:**

2000.0 ohms per volt

**Dial Scale Marking Color:**

Black single indicator all ranges

**Accuracy In Percent:**

-5.0 to 5.0 at full scale single indicator all ranges

**Unable To Decode:**

Unable to decode or unable to decode

**Meter Depth Behind Mounting Flange:**

1.081 inches

**Meter Body Diameter Behind Mounting Flange:**

2.210 inches

**Movement Type:**

Moving coil, permanent magnet

**Background Color:**

White single indicator all ranges

**Pointer Color:**

Black single indicator all ranges

**Power Source:**

External

**Mounting Facility Type And Quantity:**

3 screw and 3 unthreaded hole

**Scale Graduation Type:**

Linear single indicator all ranges

**Measurement Range:**

+0.0 to 60.0 volts, ac single indicator 2nd range

**Scale Selection Method:**

Terminal

**Features Provided:**

Magnetic shield and rectifier circuit and zero adjuster

**Movement Suspension Method:**

Jewel pivot base

**Circuit Attachment Method And Quantity:**

2 solder lug

**Special Features:**

Ruggedized

**Material:**

Steel

**Nuclear Hardness Critical Feature:**

Nonhardened

**Style Designator:**

Round flush mtg

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiiig:**

A310a0