

View Online at <https://aerobasegroup.com/nsn/6625-00-773-0163>

Circuit Current For Which Designed:

Ac

Overall Length:

2.118 inches

Mounting Hole Diameter:

Between 0.120 inches and 0.130 inches

Scale Division Quantity:

60 single indicator 2nd range

Overall Diameter:

2.695 inches

Environmental Protection:

Cold resistant and heat resistant and shock resistant and vibration resistant

Mounting Bolt Circle Diameter:

2.440 inches

Furnished Items And Quantity:

Nut 3; lockwasher 3

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Three hole/stud bolt circle

Sensitivity Rating:

2000.0 ohms per volt

Dial Scale Marking Color:

Black single indicator all ranges

Accuracy In Percent:

-5.0 to 5.0 at full scale single indicator all ranges

Unable To Decode:

Unable to decode or unable to decode

Meter Depth Behind Mounting Flange:

1.081 inches

Meter Body Diameter Behind Mounting Flange:

2.210 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator all ranges

Pointer Color:

Black single indicator all ranges

Power Source:

External

Mounting Facility Type And Quantity:

3 screw and 3 unthreaded hole

Scale Graduation Type:

Linear single indicator all ranges

Measurement Range:

+0.0 to 60.0 volts, ac single indicator 2nd range

Scale Selection Method:

Terminal

Features Provided:

Magnetic shield and rectifier circuit and zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 solder lug

Special Features:

Ruggedized

Material:

Steel

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Round flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiiig:

A310a0