NSN 6625-00-773-2832

Ammeter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-773-2832

| Circuit Current For Which Designed: |
|--|
| Dc |
| Dielectric Withstanding Voltage In Volts: |
| 3000.0 |
| Overall Length: |
| 2.060 inches |
| Scale Division Quantity: |
| 100 single indicator single range |
| Mounting Stud Length: |
| 0.500 inches |
| Overall Diameter: |
| 3.510 inches |
| Mounting Bolt Circle Diameter: |
| 3.160 inches |
| Indicator Type: |
| Dial w/pointer |
| Installation Design: |
| Panel |
| Mounting Arrangement Style: |
| Three hole/stud bolt circle |
| Dial Scale Marking Color: |
| Black single indicator single range |
| Accuracy In Percent: |
| -1.0/+1.0 at full scale single indicator single range |
| Meter Depth Behind Mounting Flange: |
| 1.660 inches |
| Meter Body Diameter Behind Mounting Flange: |
| 2.800 inches |
| Background Color: |
| White single indicator single range |
| Pointer Color: |
| Black single indicator single range |
| Mounting Facility Type And Quantity: |
| 3 threaded stud |
| Scale Graduation Type: |
| Linear single indicator single range |
| Measurement Range: |
| +0.0/+500.0 milliamperes, dc single indicator single range |
| Mounting Stud Diameter: |
| 0.138 inches |
| Circuit Attachment Method And Quantity: |

2 binding post

NSN 6625-00-773-2832

Ammeter - Page 2 of 2



| Material: |
|-----------------------------------|
| Steel |
| Nuclear Hardness Critical Feature |
| Nonhardened |
| Surface Treatment: |
| Cadmium |
| Style Designator: |
| Round flush mtg |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| Yes - demil/mli |

Fiig: A310a0