

View Online at <https://aerobasegroup.com/nsn/6625-00-774-6520>

**Circuit Current For Which Designed:**

Dc

**Overall Length:**

1.375 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

4.000 inches

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

3.560 inches

**Overall Height:**

4.200 inches

**Overall Width:**

4.660 inches

**Scale Division Quantity:**

20 single indicator single range

**Mounting Stud Length:**

0.625 inches

**Environmental Protection:**

Dustproof

**Furnished Items And Quantity:**

Mounting hardware 4

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Four hole/stud rectangular/square

**Sensitivity Rating:**

1000.0 ohms per volt

**Dial Scale Marking Color:**

Black single indicator single range

**Accuracy In Percent:**

-2.0 to 2.0 at full scale single indicator single range

**Meter Depth Behind Mounting Flange:**

1.000 inches

**Meter Body Diameter Behind Mounting Flange:**

2.750 inches

**Movement Type:**

Moving coil, permanent magnet

**Background Color:**

White single indicator single range

**Pointer Color:**

Black single indicator single range

**Power Source:**

External

**Mounting Facility Type And Quantity:**

4 threaded stud

**Scale Graduation Type:**

Linear single indicator single range

**Measurement Range:**

+0.0 to 1.0 kilovolts, dc single indicator single range

**Mounting Stud Diameter:**

0.135 inches

**Scale Selection Method:**

Switch

**Features Provided:**

Zero adjuster

**Movement Suspension Method:**

Jewel pivot base

**Circuit Attachment Method And Quantity:**

2 binding post

**Material:**

Plastic

**Nuclear Hardness Critical Feature:**

Nonhardened

**Surface Treatment:**

Enamel lusterless

**Style Designator:**

Rectangular flush mtg

**Fsc Application Data:**

Test set electronic

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A310a0