

View Online at <https://aerobasegroup.com/nsn/6625-00-775-1183>

Circuit Current For Which Designed:

Ac

Overall Length:

5.188 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

6.188 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

5.688 inches

Overall Height:

6.625 inches

Overall Width:

7.031 inches

Mounting Hole Diameter:

0.188 inches

Frequency Rating:

400.0 hertz

Environmental Protection:

Cold resistant and dustproof and heat resistant and humidity proof and shock resistant and vibration resistant and watertight

Furnished Items And Quantity:

External multipliers 4

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Sensitivity Rating:

35.0 volts

Dial Scale Marking Color:

Black single indicator all ranges

Accuracy In Percent:

-1.0 to 1.0 at full scale single indicator all ranges

Unable To Decode:

Unable to decode or unable to decode

Meter Depth Behind Mounting Flange:

3.469 inches

Meter Body Width Behind Mounting Flange:

5.875 inches

Movement Type:

Electrodynamometer

Background Color:

White single indicator all ranges

Pointer Color:

Black single indicator all ranges

Power Source:

External

Mounting Facility Type And Quantity:

6 unthreaded hole

Scale Graduation Type:

Nonlinear single indicator all ranges

Measurement Range:

+0.0 to 35.0 volts, dc single indicator 4th range

Scale Selection Method:

Switch

Meter Body Height Behind Mounting Flange:

5.375 inches

Features Provided:

Zero adjuster

Circuit Attachment Method And Quantity:

2 threaded stud

Special Features:

Ruggedized

Material:

Steel

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Enamel

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A310a0