NSN 6625-00-775-1874

Signal Generator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-775-1874

Mounting Type:

Bench

Overall Length:

14.750 inches

Overall Height:

11.250 inches

Overall Width:

11.125 inches

Current Type:

Ac

Frequency Rating:

Between 50.0 hertz and 1000.0 hertz

Case Material:

Aluminum

Case Surface Treatment:

Enameled

Frequency Range Rating:

+0.010/+50.000 megahertz

Accessory Component Quantity:

1 and 1 and 1 and 1 and 1 and 1

Accessory Controlling Agency:

Jetds; jetds; jetds; jetds; jetds; jetds; jetds

Accessory Identifying Number:

Cn-223/urm-25j type no. And cn-224/urm-25j type no. And sm-35/urm-25 type no. And cx-1363/u type no. And cg-409/u/4ft.2in/ type no. And

cg-409/u6in./ type no. And ug-684a/u type no.

Joint Electronics Type Designation System Item Name:

Generator, signal

Joint Electronics Type Designation System Item Type Number:

Type no. Anurm25jw0spares

Internal Battery Accommodation:

Not included

Output Impedance Rating:

0.5 kilohms and 50.0 kilohms

Voltage Rating:

115.0 volts

Frequency Band Quantity:

8

Modulation Type:

Am

Accessory Component Name:

Fixed attenuator 1; fixed attenuator 1; antenna simualator 1; lead, test 1; cord 1; cord 1; connector, adapter 1

Calibration Accuracy Rating:

Porm 0.5 pct to 1 mhz, porm 0.05 pct 1 mhz to 50 mhz

NSN 6625-00-775-1874 Signal Generator - Page 2 of 2



Crystal Controlled Feature:
Not provided
Calibrated Signal Output Range:
0.1 uv to 0.1 v
Signal Output Constancy:
Porm 10 pct maximum variation throughout freq range
Modulator Location:
External
Modulated Frequency Rating:
Between 0.010 kilohertz and 15.0 kilohertz
Modulation Degree:
50.0 percent
Phase:
Single
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
Т320-ј