

View Online at <https://aerobasegroup.com/nsn/6625-00-775-1874>

**Mounting Type:**

Bench

**Overall Length:**

14.750 inches

**Overall Height:**

11.250 inches

**Overall Width:**

11.125 inches

**Current Type:**

Ac

**Frequency Rating:**

Between 50.0 hertz and 1000.0 hertz

**Case Material:**

Aluminum

**Case Surface Treatment:**

Enameled

**Frequency Range Rating:**

+0.010/+50.000 megahertz

**Accessory Component Quantity:**

1 and 1 and 1 and 1 and 1 and 1 and 1

**Accessory Controlling Agency:**

Jetds; jetds; jetds; jetds; jetds; jetds; jetds

**Accessory Identifying Number:**

Cn-223/urm-25j type no. And cn-224/urm-25j type no. And sm-35/urm-25 type no. And cx-1363/u type no. And cg-409/u/4ft.2in/ type no. And cg-409/u6in./ type no. And ug-684a/u type no.

**Joint Electronics Type Designation System Item Name:**

Generator, signal

**Joint Electronics Type Designation System Item Type Number:**

Type no. Anurm25jw0spares

**Internal Battery Accommodation:**

Not included

**Output Impedance Rating:**

0.5 kilohms and 50.0 kilohms

**Voltage Rating:**

115.0 volts

**Frequency Band Quantity:**

8

**Modulation Type:**

Am

**Accessory Component Name:**

Fixed attenuator 1; fixed attenuator 1; antenna simualator 1; lead, test 1; cord 1; cord 1; connector, adapter 1

**Calibration Accuracy Rating:**

Porm 0.5 pct to 1 mhz, porm 0.05 pct 1 mhz to 50 mhz

**Crystal Controlled Feature:**

Not provided

**Calibrated Signal Output Range:**

0.1 uv to 0.1 v

**Signal Output Constancy:**

Porm 10 pct maximum variation throughout freq range

**Modulator Location:**

External

**Modulated Frequency Rating:**

Between 0.010 kilohertz and 15.0 kilohertz

**Modulation Degree:**

50.0 percent

**Phase:**

Single

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

T320-j