NSN 6625-00-775-4297

Arbitrary Scale Meter - Page 1 of 2



0-775-4297

| View Online at https://aerobasegroup.com/nsn/6625-00 |
|---|
| Circuit Current For Which Designed: |
| Overall Length: |
| 2.087 inches |
| Mounting Hole Diameter: |
| Between 0.143 inches and 0.157 inches |
| Scale Division Quantity: |
| 2 single indicator single range |
| Overall Diameter: |
| 3.510 inches |
| Environmental Protection: |
| Shock resistant and vibration resistant |
| Mounting Bolt Circle Diameter: |
| 3.160 inches |
| Furnished Items And Quantity: |
| Nut 3; washer 5 |
| Indicator Type: |
| Dial w/pointer |
| Installation Design: |
| Panel |
| Mounting Arrangement Style: |
| Three hole/stud bolt circle |
| Sensitivity Rating: |
| 200.0 microamperes |
| Dial Scale Marking Color: |
| Black and red single indicator single range |
| Accuracy In Percent: |
| -3.0 to 3.0 at full scale single indicator single range |
| Meter Depth Behind Mounting Flange: |
| 1.405 inches |
| Meter Body Diameter Behind Mounting Flange: |
| 2.800 inches |
| Movement Type: |
| Moving coil, permanent magnet |
| Background Color: |
| White single indicator single range |
| Pointer Color: |
| Black single indicator single range |
| Scale Marking: |
| Red line center of scale |
| Mounting Facility Type And Quantity: |

3 screw and 3 unthreaded hole

NSN 6625-00-775-4297

Arbitrary Scale Meter - Page 2 of 2



| Scale Graduation Type: |
|---|
| Linear single indicator single range |
| Features Provided: |
| Zero adjuster |
| Movement Suspension Method: |
| Jewel pivot base |
| Circuit Attachment Method And Quantity: |
| 2 solder lug and 2 threaded stud |
| Special Features: |
| Ruggedized |
| Material: |
| Steel |
| Nuclear Hardness Critical Feature: |
| Nonhardened |
| Special Test Features: |
| Conforms to mil-m-10304 |
| Style Designator: |
| Round flush mtg |
| Fsc Application Data: |
| Test set, elect. Equip. |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A310a0 |