Standing Wave Ratio Meter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-779-9561

Circuit Current For Which Designed:
Dc
Dielectric Withstanding Voltage In Volts:
2000.0
Overall Length:
2.280 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
4.000 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
3.560 inches
Overall Height:
4.200 inches
Overall Width:
4.660 inches
Scale Division Quantity:
20 single indicator single range
Mounting Stud Length:
0.650 inches
Environmental Protection:
Dust resistant
Indicator Type:
Dial w/pointer
Installation Design:
Panel
Mounting Arrangement Style:
Four hole/stud rectangular/square
Sensitivity Rating:
200.0 microamperes
Dial Scale Marking Color:
Black single indicator single range
Accuracy In Percent:
-5.0 to 5.0 at full scale single indicator single range
Unable To Decode:
Unable to decode or unable to decode
Meter Depth Behind Mounting Flange:
1.680 inches
Meter Body Diameter Behind Mounting Flange:
2.750 inches
Movement Type:
Moving coil, permanent magnet
Background Color:
White single indicator single range

Standing Wave Ratio Meter - Page 2 of 2



Black	single indicator single range
	ting Facility Type And Quantity:
	aded stud
	Graduation Type:
	single indicator single range
	urement Range:
	o 200.0 microamperes, dc single indicator single range
	ting Stud Diameter:
	inches
Featu	res Provided:
Magne	etic shield and zero adjuster
Move	ment Suspension Method:
Jewel	pivot base
Circui	it Attachment Method And Quantity:
2 threa	aded stud
Speci	al Markings:
Cal ab	ove 3.0 point on scale, swr below scale
Mater	ial:
Plastic	
Nucle	ar Hardness Critical Feature:
Nonha	ardened
Surfa	ce Treatment:
Paint	
	Designator:
	ngular flush mtg
	pplication Data:
	et, electronic equipment
Shelf	Life:
N/a	
Unit C	Of Measure:
	itarization:
No	
Fiig:	