

View Online at <https://aerobasegroup.com/nsn/6625-00-781-5769>

Circuit Current For Which Designed:

Dc

Overall Depth:

3.500 inches

Overall Length:

6.000 inches

Overall Width:

6.000 inches

Scale Division Quantity:

100 single indicator all ranges

End Application:

An/gy2-15

Furnished Items And Quantity:

Three in. Test leads 2; probes 2; leather strap 1

Indicator Type:

Dial w/pointer

Installation Design:

Hand held

Sensitivity Rating:

50.0 millivolts

Dial Scale Marking Color:

Black single indicator all ranges

Accuracy In Percent:

-0.5/+0.5 at full scale single indicator all ranges

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator all ranges

Pointer Color:

Black single indicator all ranges

Scale Graduation Type:

Linear single indicator all ranges

Measurement Range:

+0.0/+50.0 amperes, dc single indicator 3rd range

Scale Selection Method:

Terminal

Features Provided:

Magnetic shield and zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 clip

Functional Classification:

Aa-1.2

Special Features:

Steel six line; oper temp porm 50deg c; insulation test: 2600 vrms terminals to case one minute; scale length: 5.2 in.; scale arc 90 deg.; resistance 100 mv drop ; 2 handles

Material:

Steel

Reference Data And Literature:

To 33a1-12-946-1

Surface Treatment:

Copper alloy

Special Test Features:

Multiple range 300/30/3

Style Designator:

Portable

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A310a0