

View Online at <https://aerobasegroup.com/nsn/6625-00-781-5769>

**Circuit Current For Which Designed:**

Dc

**Overall Depth:**

3.500 inches

**Overall Length:**

6.000 inches

**Overall Width:**

6.000 inches

**Scale Division Quantity:**

100 single indicator all ranges

**End Application:**

An/gy2-15

**Furnished Items And Quantity:**

Three in. Test leads 2; probes 2; leather strap 1

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Hand held

**Sensitivity Rating:**

50.0 millivolts

**Dial Scale Marking Color:**

Black single indicator all ranges

**Accuracy In Percent:**

-0.5/+0.5 at full scale single indicator all ranges

**Movement Type:**

Moving coil, permanent magnet

**Background Color:**

White single indicator all ranges

**Pointer Color:**

Black single indicator all ranges

**Scale Graduation Type:**

Linear single indicator all ranges

**Measurement Range:**

+0.0/+50.0 amperes, dc single indicator 3rd range

**Scale Selection Method:**

Terminal

**Features Provided:**

Magnetic shield and zero adjuster

**Movement Suspension Method:**

Jewel pivot base

**Circuit Attachment Method And Quantity:**

2 clip

**Functional Classification:**

Aa-1.2

**Special Features:**

Steel six line; oper temp porm 50deg c; insulation test: 2600 vrms terminals to case one minute; scale length: 5.2 in.; scale arc 90 deg.; resistance 100 mv drop ; 2 handles

**Material:**

Steel

**Reference Data And Literature:**

To 33a1-12-946-1

**Surface Treatment:**

Copper alloy

**Special Test Features:**

Multiple range 300/30/3

**Style Designator:**

Portable

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A310a0