NSN 6625-00-782-1176

Voltmeter - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/6625-00-782-1176

| Circuit Current For Which Designed: |
|---|
| Dc |
| Overall Length: |
| 2.000 inches |
| Mounting Hole Diameter: |
| 0.120 inches |
| Overall Diameter: |
| 2.690 inches |
| Mounting Bolt Circle Diameter: |
| 2.440 inches |
| Installation Design: |
| Panel |
| Mounting Arrangement Style: |
| Three hole/stud bolt circle |
| Dial Scale Marking Color: |
| Black single indicator single range |
| Accuracy In Percent: |
| -2.0/+2.0 at full scale single indicator all ranges |
| Meter Depth Behind Mounting Flange: |
| 1.600 inches |
| |
| Meter Body Diameter Behind Mounting Flange: |
| Meter Body Diameter Behind Mounting Flange: 2.210 inches |
| |
| 2.210 inches |
| 2.210 inches Background Color: |
| 2.210 inches Background Color: White single indicator single range |
| 2.210 inches Background Color: White single indicator single range Mounting Facility Type And Quantity: |
| 2.210 inches Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 unthreaded hole |
| 2.210 inches Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 unthreaded hole Features Provided: |
| 2.210 inches Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 unthreaded hole Features Provided: Magnetic shield |
| 2.210 inches Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 unthreaded hole Features Provided: Magnetic shield Circuit Attachment Method And Quantity: |
| 2.210 inches Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 unthreaded hole Features Provided: Magnetic shield Circuit Attachment Method And Quantity: 2 solderless lug |
| 2.210 inches Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 unthreaded hole Features Provided: Magnetic shield Circuit Attachment Method And Quantity: 2 solderless lug Style Designator: |
| 2.210 inches Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 unthreaded hole Features Provided: Magnetic shield Circuit Attachment Method And Quantity: 2 solderless lug Style Designator: Round flush mtg |
| 2.210 inches Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 unthreaded hole Features Provided: Magnetic shield Circuit Attachment Method And Quantity: 2 solderless lug Style Designator: Round flush mtg Shelf Life: |
| 2.210 inches Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 unthreaded hole Features Provided: Magnetic shield Circuit Attachment Method And Quantity: 2 solderless lug Style Designator: Round flush mtg Shelf Life: N/a |
| 2.210 inches Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 unthreaded hole Features Provided: Magnetic shield Circuit Attachment Method And Quantity: 2 solderless lug Style Designator: Round flush mtg Shelf Life: N/a |
| 2.210 inches Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 unthreaded hole Features Provided: Magnetic shield Circuit Attachment Method And Quantity: 2 solderless lug Style Designator: Round flush mtg Shelf Life: N/a Unit Of Measure: |
| 2.210 inches Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 unthreaded hole Features Provided: Magnetic shield Circuit Attachment Method And Quantity: 2 solderless lug Style Designator: Round flush mtg Shelf Life: N/a Unit Of Measure: Demilitarization: |