NSN 6625-00-782-5257

Ammeter - Page 1 of 2

Dc

Overall Length: 1.995 inches

Mounting Hole Diameter:

Scale Division Quantity:

Circuit Current For Which Designed:

Between 0.120 inches and 0.130 inches



View Online at https://aerobasegroup.com/nsn/6625-00-782-5257

24 single indicator single range
Overall Diameter:
2.695 inches
Environmental Protection:
Dust resistant and humidity resistant and shock resistant and vibration resistant and water resistant
Mounting Bolt Circle Diameter:
2.440 inches
Furnished Items And Quantity:
Nut 2; washer 2
Indicator Type:
Dial w/pointer
Installation Design:
Panel
Mounting Arrangement Style:
Three hole/stud bolt circle
Sensitivity Rating:
1.0 milliamperes
Dial Scale Marking Color:
Black single indicator single range
Accuracy In Percent:
-2.0/+2.0 at full scale single indicator single range
Unable To Decode:
Unable to decode or unable to decode
Meter Depth Behind Mounting Flange:
1.220 inches
Meter Body Diameter Behind Mounting Flange:
2.050 inches
Movement Type:
Moving coil, permanent magnet
Background Color:
White single indicator single range
Pointer Color:
Black single indicator single range
Power Source:
External

NSN 6625-00-782-5257

Ammeter - Page 2 of 2



Mounting Facility Type And Quantity:
3 unthreaded hole
Scale Graduation Type:
Linear single indicator single range
Measurement Range:
+0.0/+1.2 microamperes, dc single indicator single range
Features Provided:
Magnetic shield and nonglare glass and zero adjuster
Movement Suspension Method:
Jewel pivot base
Circuit Attachment Method And Quantity:
2 solder lug and 2 threaded stud
Special Features:
Ruggedized
Special Markings:
Output r.M.S.
Material:
Steel
Nuclear Hardness Critical Feature:
Nonhardened
Surface Treatment:
Cadmium and chromate and enamel semigloss
Style Designator:
Round flush mtg
Fsc Application Data:
Test set, elect. Equip.
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:
A310a0