

View Online at <https://aerobasegroup.com/nsn/6625-00-782-7541>

Current Type:

Ac

Frequency Rating:

60.0 hertz

Accessory Component Quantity:

2 and 1 and 4 and 1 and 1 and 1 and 2 and 2 and 2 and 1

Accessory Controlling Agency:

Photron instrument co

Accessory Identifying Number:

D12 model no. And 203 part no. And 11532 part no. And 1898 part no. And 1899 part no. And 1897 part no. And 312003 part no. And 15740 part no. And 15755 part no. And 500-12 part no.

Installation Design:

Portable

Voltage Rating:

Between 105.0 volts and 125.0 volts

Recording Method:

Ink chart paper

Accessory Component Name:

Preamplifier; chart paper roll; ink cartridge; gram gage; syringe; pen mounting tool; fuse 3 amp; electrical connector; connector clamp; instruction book

Recording Channel Quantity:

2

Recording Frequency Range In Hertz:

+0.0/+100.0

Sensitivity Deflection Per Volt In Millimeters:

100.00

Chart Speed:

1.0 millimeters per second and 5.0 millimeters per second and 25.0 millimeters per second and 125.0 millimeters per second

Amplitude Deflection Frequency Range:

40mm at 20 hz; 38mm at 40 hz; 25mm at 70 hz; 15mm at 1000 hz

Event Marker:

Provided

Phase:

Single

Special Features:

10.375 in. By 13.500 in. By 15.000 in. O/a dim

Fsc Application Data:

Oscillograph, except specially designed

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T179-q