

View Online at <https://aerobasegroup.com/nsn/6625-00-783-5145>

**Circuit Current For Which Designed:**

Ac

**Overall Length:**

1.625 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

Between 1.306 inches and 1.318 inches

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

Between 1.306 inches and 1.318 inches

**Overall Height:**

Between 1.734 inches and 1.766 inches

**Overall Width:**

Between 1.734 inches and 1.766 inches

**Mounting Hole Diameter:**

0.125 inches

**Environmental Protection:**

Water resistant

**Furnished Items And Quantity:**

Gasket 1

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Four hole/stud rectangular/square

**Frequency Response Range:**

+0.025 to 16.000 kilohertz

**Dial Scale Marking Color:**

Black and red single indicator 2nd range

**Accuracy In Percent:**

-3.0 to 3.0 at full scale single indicator all ranges

**Meter Depth Behind Mounting Flange:**

1.000 inches

**Meter Body Diameter Behind Mounting Flange:**

1.510 inches

**Movement Type:**

Moving iron vane

**Background Color:**

White single indicator all ranges

**Pointer Color:**

Black single indicator all ranges

**Power Source:**

External

**Mounting Facility Type And Quantity:**

4 unthreaded hole

**Scale Graduation Type:**

Nonlinear single indicator all ranges

**Measurement Range:**

-30.0 to 3.0 voice units single indicator 2nd range

**Features Provided:**

Luminous scale marking

**Movement Suspension Method:**

Taut band

**Circuit Attachment Method And Quantity:**

2 solderless lug

**Material:**

Steel

**Nuclear Hardness Critical Feature:**

Nonhardened

**Style Designator:**

Rectangular flush mtg

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A310a0