

View Online at <https://aerobasegroup.com/nsn/6625-00-783-7217>

**Current Type:**

Ac

**Frequency Rating:**

60.0 hertz output

**Installation Design:**

Portable

**Voltage Rating:**

115.0 volts output

**Recording Method:**

Ink chart paper

**Recording Channel Quantity:**

2

**Recording Frequency Range In Hertz:**

+0.0 to 100.0

**Sensitivity Deflection Per Volt In Millimeters:**

100.00

**Chart Speed:**

1.0 millimeters per second and 5.0 millimeters per second and 15.0 millimeters per second and 125.0 millimeters per second

**Amplitude Deflection Frequency Range:**

40mm at 0 to 40 hz; 20mm at 0 to 70 hz; 10mm at 0 to 70 hz

**Event Marker:**

Provided

**Phase:**

Single output

**Functional Classification:**

Aa-3.3

**Special Features:**

12 in. By 12-5/8 in. By 3-1/2 in. O/a dim

**Functional Description:**

Records specific timed outputs from the amplifier assembly, the transfer function assembly and the pulser assembly of the gam-72 flight control system

**Cognizant Service:**

Usaf

**Entry Date:**

70-04-01

**Reference Data And Literature:**

T.O. 33d7-12-4-1

**Relationship To Similar Equipment:**

When exhausted use 6625000182184

**Fsc Application Data:**

Oscillograph, except specially designed

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

T179-q