

View Online at <https://aerobasegroup.com/nsn/6625-00-783-7217>

Current Type:

Ac

Frequency Rating:

60.0 hertz output

Installation Design:

Portable

Voltage Rating:

115.0 volts output

Recording Method:

Ink chart paper

Recording Channel Quantity:

2

Recording Frequency Range In Hertz:

+0.0 to 100.0

Sensitivity Deflection Per Volt In Millimeters:

100.00

Chart Speed:

1.0 millimeters per second and 5.0 millimeters per second and 15.0 millimeters per second and 125.0 millimeters per second

Amplitude Deflection Frequency Range:

40mm at 0 to 40 hz; 20mm at 0 to 70 hz; 10mm at 0 to 70 hz

Event Marker:

Provided

Phase:

Single output

Functional Classification:

Aa-3.3

Special Features:

12 in. By 12-5/8 in. By 3-1/2 in. O/a dim

Functional Description:

Records specific timed outputs from the amplifier assembly, the transfer function assembly and the pulser assembly of the gam-72 flight control system

Cognizant Service:

Usaf

Entry Date:

70-04-01

Reference Data And Literature:

T.O. 33d7-12-4-1

Relationship To Similar Equipment:

When exhausted use 6625000182184

Fsc Application Data:

Oscillograph, except specially designed

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T179-q