NSN 6625-00-784-5230

Ammeter - Page 1 of 2

Dc

Overall Length: 1.210 inches

Circuit Current For Which Designed:



View Online at https://aerobasegroup.com/nsn/6625-00-784-5230

| Scale Division Quantity: |
|---|
| 5 single indicator single range |
| Overall Diameter: |
| 2.300 inches |
| Environmental Protection: |
| Dustproof |
| Furnished Items And Quantity: |
| Mounting hardware 6 |
| Indicator Type: |
| Dial w/pointer |
| Installation Design: |
| Panel |
| Dial Scale Marking Color: |
| White single indicator single range |
| Accuracy In Percent: |
| -2.0/+2.0 at full scale single indicator single range |
| Meter Depth Behind Mounting Flange: |
| 1.020 inches |
| Meter Body Diameter Behind Mounting Flange: |
| 2.080 inches |
| Movement Type: |
| Moving iron vane |
| Background Color: |
| Black single indicator single range |
| Pointer Color: |
| White single indicator single range |
| Mounting Facility Type And Quantity: |
| 1 clamp |
| Scale Graduation Type: |
| Linear single indicator single range |
| Measurement Range: |
| -100.0/+100.0 amperes, dc single indicator single range |
| Scale Selection Method: |
| Terminal |
| Features Provided: |
| Self-illumination facility |
| Movement Suspension Method: |
| Taut band |

NSN 6625-00-784-5230

Ammeter - Page 2 of 2

A310a0



| Circuit Attachment Method And Quantity: |
|--|
| 2 clip |
| Special Features: |
| Capable of satisfactory operation at ambient temp of minus 65 degrees f to plus 160 degrees f i/a/w proceedure 1 of mil-e-4970 and rain, |
| sand, dust and salt air atmosphere |
| Special Markings: |
| Red band 100 to 0 |
| Material: |
| Steel |
| Nuclear Hardness Critical Feature: |
| Nonhardened |
| Style Designator: |
| Round flush mtg |
| Fsc Application Data: |
| Test set electronic |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |