

View Online at <https://aerobasegroup.com/nsn/6625-00-787-6783>

Circuit Current For Which Designed:

Ac

Overall Length:

2.000 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.250 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.250 inches

Overall Height:

3.120 inches

Overall Width:

3.000 inches

Scale Division Quantity:

60 single indicator single range

Mounting Stud Length:

0.530 inches

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Frequency Response Range:

+25.000 to 125.000 hertz

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0 to 2.0 at full scale single indicator single range

Unable To Decode:

Unable to decode or unable to decode

Meter Depth Behind Mounting Flange:

1.450 inches

Meter Body Diameter Behind Mounting Flange:

2.730 inches

Movement Type:

Moving iron vane

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

4 threaded stud

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+0.0 to 300.0 volts, ac single indicator single range

Mounting Stud Diameter:

0.250 inches

Features Provided:

Magnetic shield and zero adjuster

Circuit Attachment Method And Quantity:

2 threaded stud

Material:

Plastic

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular flush mtg

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0