

View Online at <https://aerobasegroup.com/nsn/6625-00-789-0436>

Circuit Current For Which Designed:

Dc

Overall Length:

1.251 inches

Overall Diameter:

1.250 inches

End Application:

Oliver perry class ffg, arleigh burke class ddg, spruance class dd (963), landing craft air cushion (lcac), Forrestal class cv, Nimitz class cvn, Tarawa class LHA, Ticonderoga class CG (47), Wasp class LHD

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0 to 2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

0.901 inches

Meter Body Diameter Behind Mounting Flange:

1.000 inches

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

1 threaded body

Scale Graduation Type:

Nonlinear single indicator single range

Measurement Range:

-10.0 to 6.0 decibels single indicator single range

Scale Selection Method:

Terminal

Features Provided:

Magnetic shield

Criticality Code Justification:

Feat

Circuit Attachment Method And Quantity:

2 solderless lug

Special Features:

Weapon system essential

Material:

Steel

Style Designator:

Round flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0