

View Online at <https://aerobasegroup.com/nsn/6625-00-789-0436>

**Circuit Current For Which Designed:**

Dc

**Overall Length:**

1.251 inches

**Overall Diameter:**

1.250 inches

**End Application:**

Oliver perry class ffg, arleigh burke class ddg, spruance class dd (963), landing craft air cushion (lcac), Forrestal class cv, Nimitz class cvn, Tarawa class LHA, Ticonderoga class CG (47), Wasp class LHD

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Dial Scale Marking Color:**

Black single indicator single range

**Accuracy In Percent:**

-2.0 to 2.0 at full scale single indicator single range

**Meter Depth Behind Mounting Flange:**

0.901 inches

**Meter Body Diameter Behind Mounting Flange:**

1.000 inches

**Background Color:**

White single indicator single range

**Pointer Color:**

Black single indicator single range

**Power Source:**

External

**Mounting Facility Type And Quantity:**

1 threaded body

**Scale Graduation Type:**

Nonlinear single indicator single range

**Measurement Range:**

-10.0 to 6.0 decibels single indicator single range

**Scale Selection Method:**

Terminal

**Features Provided:**

Magnetic shield

**Criticality Code Justification:**

Feat

**Circuit Attachment Method And Quantity:**

2 solderless lug

**Special Features:**

Weapon system essential

**Material:**

Steel

**Style Designator:**

Round flush mtg

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A310a0