

View Online at <https://aerobasegroup.com/nsn/6625-00-794-3878>

**Circuit Current For Which Designed:**

Ac

**Overall Length:**

3.344 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

5.250 inches

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

3.000 inches

**Overall Height:**

4.406 inches

**Overall Width:**

5.844 inches

**Scale Division Quantity:**

100 single indicator 1st range

**Mounting Stud Length:**

0.500 inches

**Furnished Items And Quantity:**

Shunt wire 1

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Four hole/stud rectangular/square

**Sensitivity Rating:**

500.0 microamperes

**Dial Scale Marking Color:**

Red single indicator 1st range

**Accuracy In Percent:**

-2.0 to 2.0 at full scale single indicator all ranges

**Meter Depth Behind Mounting Flange:**

1.281 inches

**Meter Body Diameter Behind Mounting Flange:**

2.625 inches

**Movement Type:**

Moving coil, permanent magnet

**Background Color:**

White single indicator all ranges

**Pointer Color:**

Black single indicator all ranges

**Power Source:**

External

**Mounting Facility Type And Quantity:**

4 threaded stud

**Scale Graduation Type:**

Nonlinear single indicator 2nd range

**Measurement Range:**

+1.0 to 10.0 volts, root mean square single indicator 2nd range

**Mounting Stud Diameter:**

0.112 inches

**Scale Selection Method:**

Terminal

**Features Provided:**

Mirror scale and zero adjuster

**Movement Suspension Method:**

Jewel pivot base

**Circuit Attachment Method And Quantity:**

2 threaded stud

**Material:**

Plastic

**Nuclear Hardness Critical Feature:**

Nonhardened

**Style Designator:**

Rectangular flush mtg

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A310a0