

View Online at <https://aerobasegroup.com/nsn/6625-00-799-9001>

Overall Length:

23.250 inches

Overall Height:

15.500 inches

Overall Width:

8.375 inches

Current Type:

Ac

Frequency Rating:

Between 48.0 hertz and 450.0 hertz

Voltage Rating:

Between 115.0 volts and 230.0 volts

Beam Quantity:

1

Screen Size:

3 in.

Sweep Circuits:

Included

Generator Driven Feature:

Not included

Sweep Frequency Range:

+0.000/+1.000 megahertz

Single Trigger Sweep Duration:

1.0 microseconds

Trigger Sweep Voltage Amplitude Rating:

10.0 volts

Trigger Sweep Polarity Switch:

Not included

Trigger Sweep Marker Intervals:

0.2 cm, 1.0 cm, and 2.5 cm

Expanded Sweep:

Not provided

Amplifier Deflection Sensitivity Provision:

Provided

Vertical Deflection Sensitivity Voltage Rating:

10.0 millivolts rms per centimeter

Horizontal Deflection Sensitivity Voltage Rating:

10.0 millivolts any acceptable minor

Input Intensity Modulation Feature:

Not provided

Plate Direct Connection Deflection Sensitivity Provision:

Provided

Direct Connection Vertical Deflection Sensitivity Voltage Rating:

10.0 volts any acceptable minor

Direct Connection Horizontal Deflection Sensitivity Voltage Rating:

14.0 volts rms per centimeter

Frequency Response Rating:

Provided

X-axis Frequency Response Rating:

Between 0.0 kilohertz and 100.0 kilohertz

Y-axis Frequency Response Rating:

Between 0.0 kilohertz and 100.0 kilohertz

Z-axis Frequency Response Rating:

Between 0.0 kilohertz and 300.0 kilohertz

Amplifier Input Impedance Rating Provision:

Provided

X-axis Input Impedance Rating:

1.0 megohms

Y-axis Input Impedance Rating:

1.0 megohms

Z-axis Input Impedance Rating:

2.0 megohms

Calibrated Screen Scale:

Not included

Trace Storage Tube:

Not included

Camera Recording Device Accommodation:

Not provided

Phase:

Single

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T320-g