NSN 6625-00-799-9001

Oscilloscope - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-799-9001

Overall Length:
23.250 inches
Overall Height:
15.500 inches
Overall Width:
8.375 inches
Current Type:
Ac
Frequency Rating:
Between 48.0 hertz and 450.0 hertz
Voltage Rating:
Between 115.0 volts and 230.0 volts
Beam Quantity:
1
Screen Size:
3 in.
Sweep Circuits:
Included
Generator Driven Feature:
Not included
Sweep Frequency Range:
+0.000/+1.000 megahertz
Single Trigger Sweep Duration:
1.0 microseconds
Trigger Sweep Voltage Amplitude Rating:
10.0 volts
Trigger Sweep Polarity Switch:
Not included
Trigger Sweep Marker Intervals:
0.2 cm, 1.0 cm, and 2.5 cm
Expanded Sweep:
Not provided
Amplifier Deflection Sensitivity Provision:
Provided
Vertical Deflection Sensitivity Voltage Rating:
10.0 millivolts rms per centimeter
Horizontal Deflection Sensitivity Voltage Rating:
10.0 millivolts any acceptable minor
Input Intensity Modulation Feature:
Not provided
Plate Direct Connection Deflection Sensitivity Provision:
Drewided

Provided

NSN 6625-00-799-9001

Oscilloscope - Page 2 of 2



Direct Connection Vertical Deflection Sensitivity Voltage Rating:
10.0 volts any acceptable minor
Direct Connection Horizontal Deflection Sensitivity Voltage Rating:
14.0 volts rms per centimeter
Frequency Response Rating:
Provided
X-axis Frequency Response Rating:
Between 0.0 kilohertz and 100.0 kilohertz
Y-axis Frequency Response Rating:
Between 0.0 kilohertz and 100.0 kilohertz
Z-axis Frequency Response Rating:
Between 0.0 kilohertz and 300.0 kilohertz
Amplifier Input Impedance Rating Provision:
Provided
X-axis Input Impedance Rating:
1.0 megohms
Y-axis Input Impedance Rating:
1.0 megohms
Z-axis Input Impedance Rating:
2.0 megohms
Calibrated Screen Scale:
Not included
Trace Storage Tube:
Not included
Camera Recording Device Accommodation:
Not provided
Phase:
Single
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
Т320-а