NSN 6625-00-800-4478

Ammeter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-800-4478

| Circuit Current For Which Designed: | | | | |
|---|--|--|--|--|
| Dc | | | | |
| Reliability Indicator: | | | | |
| Not established | | | | |
| Mounting Hole Diameter: | | | | |
| 0.156 inches | | | | |
| Scale Division Quantity: | | | | |
| 50 single indicator single range | | | | |
| Overall Diameter: | | | | |
| 3.500 inches | | | | |
| Mounting Bolt Circle Diameter: | | | | |
| 3.156 inches | | | | |
| Installation Design: | | | | |
| Panel | | | | |
| Mounting Arrangement Style: | | | | |
| Three hole/stud bolt circle | | | | |
| Sensitivity Rating: | | | | |
| 50.0 millivolts | | | | |
| Dial Scale Marking Color: | | | | |
| Black single indicator single range | | | | |
| Accuracy In Percent: | | | | |
| -2.0/+2.0 at full scale single indicator single range | | | | |
| Meter Depth Behind Mounting Flange: | | | | |
| 1.062 inches | | | | |
| Meter Body Diameter Behind Mounting Flange: | | | | |
| 2.688 inches | | | | |
| Movement Type: | | | | |
| Moving coil, permanent magnet | | | | |
| Background Color: | | | | |
| White single indicator single range | | | | |
| Mounting Facility Type And Quantity: | | | | |
| 3 unthreaded hole | | | | |
| Measurement Range: | | | | |
| +0.0/+5.0 amperes, dc single indicator single range | | | | |
| Features Provided: | | | | |
| Magnetic shield | | | | |
| Movement Suspension Method: | | | | |
| Jewel pivot base | | | | |
| Circuit Attachment Method And Quantity: | | | | |

2 threaded stud

Style Designator:

Round flush mtg

NSN 6625-00-800-4478

Ammeter - Page 2 of 2



| Fsc A | ۱qq | ication | Data: |
|-------|-----|---------|-------|
|-------|-----|---------|-------|

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0