

View Online at <https://aerobasegroup.com/nsn/6625-00-801-0054>

Circuit Current For Which Designed:

Dc

Dielectric Withstanding Voltage In Volts:

500.0

Overall Length:

2.110 inches

Overall Height:

Between 0.502 inches and 0.515 inches

Overall Width:

1.605 inches

Mounting Hole Diameter:

0.096 inches

Scale Division Quantity:

4 single indicator single range

Environmental Protection:

Cold resistant and heat resistant and humidity resistant and salt spray resistant and shock resistant and vibration resistant

Distance Between Mounting Facility Centers:

1.285 inches

Barrel Width:

1.522 inches

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Two hole/stud

Sensitivity Rating:

100.0 microamperes

Dial Scale Marking Color:

Black and green, light and red single indicator single range

Accuracy In Percent:

-2.0 to 2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

1.922 inches

Meter Body Width Behind Mounting Flange:

1.605 inches

Movement Type:

Moving coil, permanent magnet

Pointer Color:

Yellow, fluorescent single indicator single range

Scale Marking:

Zero center line mark

Mounting Facility Type And Quantity:

2 unthreaded hole

Scale Graduation Type:

Linear single indicator single range

Meter Body Height Behind Mounting Flange:

1.138 inches

Meter Barrel Depth:

1.421 inches

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 solder lug

Special Features:

Terminals marked with polarity symbols

Special Markings:

Dial scale has black band at center scale 0.020 ins wide; light green band centered, covering one half the viewed scale; red band on each end of light green band to end of scale

Material:

Plastic

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular flush mtg barrel, down

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0