

View Online at <https://aerobasegroup.com/nsn/6625-00-803-4435>

Circuit Current For Which Designed:

Ac

Overall Length:

2.900 inches

Overall Height:

3.500 inches

Overall Width:

3.500 inches

Frequency Rating:

Between 380.0 hertz and 420.0 hertz

Mounting Stud Length:

0.750 inches

Environmental Protection:

Dustproof

Mounting Bolt Circle Diameter:

3.160 inches

Furnished Items And Quantity:

Mounting hardware 5

Indicator Type:

Vibrating reed

Installation Design:

Panel

Register Quantity:

1

Mounting Arrangement Style:

Three hole/stud bolt circle

Resonant Reed Quantity:

9

Meter Depth Behind Mounting Flange:

2.500 inches

Meter Body Diameter Behind Mounting Flange:

2.180 inches

Movement Type:

Vibrating reed

Background Color:

White single indicator single range

Mounting Facility Type And Quantity:

3 threaded stud

Measurement Range:

+380.0 to 420.0 hertz single indicator single range

Mounting Stud Diameter:

0.138 inches

Scale Selection Method:

Terminal

Accuracy Rating:

0.03 pct single indicator single range

Display Color:

Black single indicator single range

Circuit Attachment Method And Quantity:

2 threaded stud

Operating Voltage Rating In Volts:

Between 100.0 ac and 130.0 ac

Material:

Steel

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Enamel semigloss

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set electronic

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A310a0