

View Online at <https://aerobasegroup.com/nsn/6625-00-803-6199>

Circuit Current For Which Designed:

Ac

Overall Length:

2.020 inches

Mounting Hole Diameter:

0.147 inches

Overall Diameter:

3.500 inches

Environmental Protection:

Dustproof

Mounting Bolt Circle Diameter:

3.160 inches

Indicator Type:

Vibrating reed

Installation Design:

Panel

Register Quantity:

1

Mounting Arrangement Style:

Three hole/stud bolt circle

Frequency Response Range:

+395.000 to 405.000 hertz

Dial Scale Marking Color:

Black single indicator single range

Resonant Reed Quantity:

11

Meter Depth Behind Mounting Flange:

1.930 inches

Meter Body Diameter Behind Mounting Flange:

2.780 inches

Movement Type:

Vibrating reed

Background Color:

White single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

3 unthreaded hole

Measurement Range:

+395.0 to 405.0 hertz single indicator single range

Scale Selection Method:

Terminal

Circuit Attachment Method And Quantity:

2 threaded stud

Operating Voltage Rating In Volts:

Between 100.0 ac and 130.0 ac

Material:

Plastic

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Enamel semigloss

Style Designator:

Round flush mtg

Fsc Application Data:

Test set electronic

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A310a0