

View Online at <https://aerobasegroup.com/nsn/6625-00-805-0796>

Circuit Current For Which Designed:

Ac

Overall Length:

2.350 inches

Mounting Hole Diameter:

0.125 inches

Frequency Rating:

60.0 hertz

Overall Diameter:

2.660 inches

Mounting Bolt Circle Diameter:

2.440 inches

Furnished Items And Quantity:

Screws 3; lock washers 3 hex nuts 3

Indicator Type:

Vibrating reed

Installation Design:

Panel

Register Quantity:

1

Mounting Arrangement Style:

Three hole/stud bolt circle

Dial Scale Marking Color:

Black single indicator single range

Resonant Reed Quantity:

9

Meter Depth Behind Mounting Flange:

2.500 inches

Meter Body Diameter Behind Mounting Flange:

2.200 inches

Movement Type:

Vibrating reed

Background Color:

White single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

3 unthreaded hole

Measurement Range:

+380.0/+420.0 hertz single indicator single range

Scale Selection Method:

Terminal

Circuit Attachment Method And Quantity:

2 threaded stud

Operating Voltage Rating In Volts:

120.0 ac

Material:

Plastic and steel

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Round flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0