

View Online at <https://aerobasegroup.com/nsn/6625-00-806-4881>

**Circuit Current For Which Designed:**

Ac

**Dielectric Withstanding Voltage In Volts:**

3000.0

**Overall Length:**

1.687 inches

**Mounting Hole Diameter:**

0.125 inches

**Overall Diameter:**

2.078 inches

**Environmental Protection:**

Airtight and dust resistant and fungus resistant and heat resistant and humidity resistant and shock resistant and vibration resistant and water resistant

**Mounting Bolt Circle Diameter:**

1.750 inches

**Furnished Items And Quantity:**

Nut 3; lockwasher 3; seal 1

**Indicator Type:**

Vibrating reed

**Installation Design:**

Panel

**Register Quantity:**

1

**Mounting Arrangement Style:**

Three hole/stud bolt circle

**Frequency Response Range:**

+58.000/+62.000 hertz

**Dial Scale Marking Color:**

Black single indicator single range

**Resonant Reed Quantity:**

5

**Meter Depth Behind Mounting Flange:**

1.562 inches

**Meter Body Diameter Behind Mounting Flange:**

1.500 inches

**Movement Type:**

Vibrating reed

**Background Color:**

White single indicator single range

**Power Source:**

External

**Mounting Facility Type And Quantity:**

3 screw and 3 unthreaded hole

**Measurement Range:**

+58.0/+62.0 hertz single indicator single range

**Scale Selection Method:**

Terminal

**Features Provided:**

Magnetic shield

**Circuit Attachment Method And Quantity:**

2 solderless lug

**Operating Voltage Rating In Volts:**

Between 100.0 ac and 130.0 ac

**Special Features:**

Ruggedized

**Special Markings:**

On back, sealed do not open

**Material:**

Plastic

**Nuclear Hardness Critical Feature:**

Nonhardened

**Surface Treatment:**

Paint

**Style Designator:**

Round flush mtg

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiiig:**

A310a0