

View Online at <https://aerobasegroup.com/nsn/6625-00-806-4881>

Circuit Current For Which Designed:

Ac

Dielectric Withstanding Voltage In Volts:

3000.0

Overall Length:

1.687 inches

Mounting Hole Diameter:

0.125 inches

Overall Diameter:

2.078 inches

Environmental Protection:

Airtight and dust resistant and fungus resistant and heat resistant and humidity resistant and shock resistant and vibration resistant and water resistant

Mounting Bolt Circle Diameter:

1.750 inches

Furnished Items And Quantity:

Nut 3; lockwasher 3; seal 1

Indicator Type:

Vibrating reed

Installation Design:

Panel

Register Quantity:

1

Mounting Arrangement Style:

Three hole/stud bolt circle

Frequency Response Range:

+58.000/+62.000 hertz

Dial Scale Marking Color:

Black single indicator single range

Resonant Reed Quantity:

5

Meter Depth Behind Mounting Flange:

1.562 inches

Meter Body Diameter Behind Mounting Flange:

1.500 inches

Movement Type:

Vibrating reed

Background Color:

White single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

3 screw and 3 unthreaded hole

Measurement Range:

+58.0/+62.0 hertz single indicator single range

Scale Selection Method:

Terminal

Features Provided:

Magnetic shield

Circuit Attachment Method And Quantity:

2 solderless lug

Operating Voltage Rating In Volts:

Between 100.0 ac and 130.0 ac

Special Features:

Ruggedized

Special Markings:

On back, sealed do not open

Material:

Plastic

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Paint

Style Designator:

Round flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiiig:

A310a0