

View Online at <https://aerobasegroup.com/nsn/6625-00-806-8759>

Circuit Current For Which Designed:

Ac

Overall Length:

Between 2.875 inches and 3.125 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.500 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.500 inches

Overall Height:

3.250 inches

Overall Width:

3.250 inches

Mounting Hole Diameter:

Between 0.168 inches and 0.172 inches

Environmental Protection:

Dust resistant and shock resistant and water resistant

Furnished Items And Quantity:

Nut 2; lock washer 2; flat washer 2

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Dial Scale Marking Color:

White single indicator single range

Accuracy In Percent:

-1.0/+1.0 at full scale single indicator single range

Unable To Decode:

Unable to decode or unable to decode

Meter Depth Behind Mounting Flange:

1.875 inches

Meter Body Diameter Behind Mounting Flange:

3.130 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

Black single indicator single range

Pointer Color:

White single indicator single range

Mounting Facility Type And Quantity:

4 unthreaded hole

Scale Graduation Type:

Nonlinear single indicator single range

Measurement Range:

+350.0/+450.0 hertz single indicator single range

Scale Selection Method:

Terminal

Movement Suspension Method:

Taut band

Circuit Attachment Method And Quantity:

2 threaded stud

Special Features:

Lance type pointer

Material:

Plastic

Nuclear Hardness Critical Feature:

Nonhardened

Special Test Features:

Porm .4 pct accuracy at 400 hz

Style Designator:

Round flush mtg w/4 tabs

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A310a0