

View Online at <https://aerobasegroup.com/nsn/6625-00-806-8759>

**Circuit Current For Which Designed:**

Ac

**Overall Length:**

Between 2.875 inches and 3.125 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

2.500 inches

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

2.500 inches

**Overall Height:**

3.250 inches

**Overall Width:**

3.250 inches

**Mounting Hole Diameter:**

Between 0.168 inches and 0.172 inches

**Environmental Protection:**

Dust resistant and shock resistant and water resistant

**Furnished Items And Quantity:**

Nut 2; lock washer 2; flat washer 2

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Four hole/stud rectangular/square

**Dial Scale Marking Color:**

White single indicator single range

**Accuracy In Percent:**

-1.0/+1.0 at full scale single indicator single range

**Unable To Decode:**

Unable to decode or unable to decode

**Meter Depth Behind Mounting Flange:**

1.875 inches

**Meter Body Diameter Behind Mounting Flange:**

3.130 inches

**Movement Type:**

Moving coil, permanent magnet

**Background Color:**

Black single indicator single range

**Pointer Color:**

White single indicator single range

**Mounting Facility Type And Quantity:**

4 unthreaded hole

**Scale Graduation Type:**

Nonlinear single indicator single range

**Measurement Range:**

+350.0/+450.0 hertz single indicator single range

**Scale Selection Method:**

Terminal

**Movement Suspension Method:**

Taut band

**Circuit Attachment Method And Quantity:**

2 threaded stud

**Special Features:**

Lance type pointer

**Material:**

Plastic

**Nuclear Hardness Critical Feature:**

Nonhardened

**Special Test Features:**

Porm .4 pct accuracy at 400 hz

**Style Designator:**

Round flush mtg w/4 tabs

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A310a0